



Product Sheet

APPLICATION

The **CJC® Filter Insert B 15/25** is used in CJC® Filters ideal for filtration of mineral and synthetic based

- hydraulic oils
- turbine lube oils
- lube oils
- honing oils
- rolling oils
- gear oils

FILTRATION CAPABILITY

• Particle Removal

All CJC® Filter Inserts have the following filtration degree:

- **3 μm absolute:**
98.7% of all solid particles $> 3 \mu\text{m}$
- **0.8 μm nominal:**
50% of all solid particles $> 0.8 \mu\text{m}$

are retained in each pass.

The dirt holding capacity of an B 15/25 Insert is **1.5 litres** of evenly distributed solids.

• Degradation Products

Oxidation by-products, resin / sludge, and varnish are retained by the cellulose material. The cellulose will retain **appr. 1 kg** of degradation products.

• Water Removal

The water absorption potential is up to 50% (i.e. **750 mL H₂O**) of the total contaminant holding capacity.

DIMENSIONS

The figures below are nominal:

Diameter:	15 cm
Height:	25 cm

COMPONENT

CJC® Filter Inserts type B consist of bonded discs. Ingredients: Wood cellulose and cotton linters.

IDENTIFICATION

To order the Filter Insert B 15/25, please use:

Article No: PA5601321

