

Part #	Model	In/Out	Diameter	Length	GPM	# of Elements
40186	Viking 1	2" NPT	12"	32½"	120	1
40187	Viking 1F	Flanged	12"	32½"	120	1
40188	Viking 2	2" NPT	12"	50½"	150	2
40189	Viking 2F	Flanged	12"	50½"	150	2
40190	Viking 3F	Flanged	24"	59¼"	300	4
40191	Viking 4F	Flanged	28"	78½"	500	8



### Applications:

- Designed for bulk fluid transfer and fueling rack filtration
- Housings and replacement elements are compatible with gasoline, ethanol blends up to E15, biodiesel blends up to B100, diesel fuel, ultra-low sulfur diesel (ULSD), and fuel oils
- Able to filter industrial fluids such as lubrication, hydraulic, synthetic oils, many solvents and thinners

### Features:

- Up to 500 gpm / 1892.7 lpm maximum flow
- 150 psi rating
- Epoxy coating inside and out
- Carbon steel housing
- Gauge ports standard

### Benefits:

- Removes common contaminants such as dirt, dust, and rust
- Increased filtering capacity
- Easy opening and access with swing lid

### 6" x 18" Elements

30066   E-1300-02	Cellulose Element	2 Micron
30008   E-1300-10	Cellulose Element	10 Micron
30009   E-1300-30	Cellulose Element	30 Micron
30204   E-1300MG-03	Microglass Element	3 Micron
30203   E-1300MG-05	Microglass Element	5 Micron
30202   E-1300MG-10	Microglass Element	10 Micron
30034   E-1300HS-10	Hydrosorb® Element	10 Micron
30037   E-1300HS-30	Hydrosorb® Element	30 Micron
30210   E-1300WM-144	Wire Mesh Element	144 Micron

NOT FOR AVIATION USE